

DURHAM COUNTY

Engineering Department

Stormwater Division

120 East Parrish Street, Durham, NC 27701 Telephone (919) 560-0739 FAX (919) 560-0740

Underground Detention Design Summary

Stormwater Management Construction Plan Review:

A complete stormwater management construction plan submittal includes a design summary for each stormwater BMP, design calculations, plans and specifications showing BMP, inlet and outlet structure details.

I. PROJECT INFORMATION Legal Name of Owner:_____ Owner Contact: _____ Phone #: (____) __-___ Owner Address:____ Deed Book ______ Page #_____ or Plat Book _____ Page#____ for BMP Property For projects with multiple basins, specify which pond this worksheet applies to: Detention provided for: _____1-year _____2-year _____10-year _____ other ______ Elevations Bottom elevation _____ ft. (invert out elevation of system) _____ ft. (invert elevation) 1-year storm orifice/weir elevation 1-year storm water surface elevation _____ ft. (elevation at the outlet of system) _____ ft. (invert elevation) 2-year storm orifice/weir elevation _____ ft. (elevation at the outlet of system) 2-year storm water surface elevation _____ ft. (invert elevation) 10-year storm orifice/weir elevation _____ ft. (elevation at the outlet of system) 10-year storm water surface elevation _____ ft. (invert of emergency spillway) Emergency spillway elevation _____ ft. (elevation of ground above outlet) **Ground Surface Elevation** Maximum Water Surface Elevation (_____-year storm) _____ ft. (elevation at the outlet of system) Areas Drainage area _____ ac. (total drainage to the facility) **Volumes** ft³ (volume detained at design storm) Total Storage Volume Provided

At BMP

	1-year		2-year		10-year		year
Inflow		cfs		cfs		cfs	cfs
Routed outflow		cfs		cfs		cfs	cfs
	At Analysi	is Point(s)	that BMP (Contribute	es to		
	1-year		-		-		year
Pre-development		cfs		cfs		cfs _	cfs
Post-development w/o detention							cfs
With detention		cts		cts		cts _	cfs
System Information							
1-year storm orifice/weir			length				
2-year storm orifice/weir			length				
10-year storm orifice/weir			length				
year storm orifice/weir			length	ft.			
Principal spillway	diameter_		-141	1	-1-		
Emergency spillway	width	п.	side slope	s:1	SIC	pe%	
The following checklist outlines requirements have been met and			-	-	ed to indica	ate the follow	ing design
Applicant's initials				cri .		1	
a. Riprap outlet	protection,	if provide	d, reduces	flow to no	on-erosive	velocities (p	rovide
calculations).	ongists of t	wa 60 inal	minimum	haadar ni	nos and try	vo 60 inch m	inimum
b. The system control perimeter pipes							
c. Manhole acce					-	ovided if field	aca.
d. Traffic bearing		-			•	a minimum	of two per
pipe run. Man							1
e. A traffic bear	•				s been pla	ced at the inl	et and outlet
of the system.							
f. Spacing of pi	_	-		_			
g. The backfill r			-		_		
h. The system is	water tigh	t for the 10)-year hydr	ostatic pro	essure calc	culated at the	inlet to the
system.	1 C	1 1	1 .	1. 6.1	.1		
i. A surface or s	sub-surface	bypass na	s been size	a to safely	y convey ti	ne maximum	required
design storm.	and mainta	,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,,	a for the ave	stam has l	aan nravi	dad	
j. An operation k. A recorded di							ne negreet
right-of-way ar	_	-				-	
l. A plan view of	_	_				DITTION (DITTI	<u>57</u> .
: = F=::= /20 ;;		0	0	1			

 m. A profile through the system and emergency bypass is provided. Water surface elevations
are shown on the profile.
 n. Outlet structure details are provided.
 o. Compaction specifications for the installation of the system are provided on the plan.

Note: Executed Stormwater Facility Operation and Maintenance Permit Agreement and payment of surety are required prior to Stormwater Permit issuance.